




# Blind Rivet Nut AFM

Aluminium

Flat head | Round shank | open



EN AW-5754 [AlMg3]

| M            | $\frac{D}{2}$ | l              | No.                           |   |
|--------------|---------------|----------------|-------------------------------|---|
| <b>M3</b>    | 0,3 - 2,0     | 8,5            | 10.850.030.200                | 500   |
|              | 2,0 - 3,5     | 11,2           | 10.850.030.350                | 500   |
| <b>D 5,0</b> | <b>k 0,8</b>  | <b>dk 7,0</b>  | <b>l<sub>1</sub> max. 6,0</b> | $\curvearrowright$ 1,0 Nm $\updownarrow$ 1500 N |
| <b>M4</b>    | 0,5 - 3,0     | 11,0           | 10.850.040.300                | 500   |
|              | 2,5 - 4,0     | 12,0           | 10.850.040.400                | 500   |
|              | 3,0 - 5,0     | 13,2           | 10.850.040.500                | 500   |
| <b>D 6,0</b> | <b>k 0,8</b>  | <b>dk 10,0</b> | <b>l<sub>1</sub> max. 8,0</b> | $\curvearrowright$ 3,0 Nm $\updownarrow$ 2600 N |
| <b>M5</b>    | 0,5 - 3,0     | 12,0           | 10.850.050.300                | 500   |
|              | 2,5 - 4,5     | 13,5           | 10.850.050.450                | 500   |
|              | 4,0 - 6,0     | 15,0           | 10.850.050.600                | 500   |
| <b>D 7,0</b> | <b>k 1,0</b>  | <b>dk 11,0</b> | <b>l<sub>1</sub> max. 9,0</b> | $\curvearrowright$ 4,0 Nm $\updownarrow$ 4300 N |

| M             | $\frac{D}{2}$ | l              | No.                            |   |
|---------------|---------------|----------------|--------------------------------|---|
| <b>M6</b>     | 0,5 - 3,0     | 14,5           | 10.850.060.300                 | 500   |
|               | 3,0 - 4,5     | 16,0           | 10.850.060.450                 | 500   |
| <b>D 9,0</b>  | <b>k 1,5</b>  | <b>dk 13,0</b> | <b>l<sub>1</sub> max. 11,0</b> | $\curvearrowright$ 6,0 Nm $\updownarrow$ 6700 N   |
| <b>M8</b>     | 0,5 - 3,0     | 17,0           | 10.850.080.300                 | 500   |
|               | 3,0 - 5,5     | 19,5           | 10.850.080.550                 | 500   |
|               | 5,5 - 7,5     | 21,5           | 10.850.080.750                 | 500   |
| <b>D 11,0</b> | <b>k 1,5</b>  | <b>dk 16,0</b> | <b>l<sub>1</sub> max. 13,5</b> | $\curvearrowright$ 18,0 Nm $\updownarrow$ 11000 N |
| <b>M10</b>    | 1,0 - 4,0     | 22,0           | 10.850.100.400                 | 250   |
|               | 3,0 - 6,0     | 24,0           | 10.850.100.600                 | 250   |
| <b>D 13,0</b> | <b>k 2,0</b>  | <b>dk 19,0</b> | <b>l<sub>1</sub> max. 16,5</b> | $\curvearrowright$ 28,0 Nm $\updownarrow$ 17500 N |
| <b>M12</b>    | 1,0 - 4,0     | 24,0           | 10.850.120.400                 | 100   |
|               | 3,5 - 7,0     | 27,0           | 10.850.120.700                 | 100   |
| <b>D 16,0</b> | <b>k 2,0</b>  | <b>dk 23,0</b> | <b>l<sub>1</sub> max. 18,5</b> | $\curvearrowright$ 45,0 Nm $\updownarrow$ 28000 N |