



EN AW-5019 [AlMg5]

d	l ⁺¹	$\frac{d}{h}$	Nr.	
3,2	6,5	0,5 - 2,0	10.900.032.065	500
	8,0	1,5 - 3,5	10.900.032.080	500
	9,5	3,0 - 5,0	10.900.032.095	500
	11,0	4,5 - 6,5	10.900.032.110	500
	12,5	6,0 - 8,0	10.900.032.125	500
dk 6,0 -0,3	dm 1,7	k 1,1 ±0,15	3,3 mm 1100 N 1450 N	
4,0	8,0	0,5 - 3,5	10.900.040.080	500
	9,5	3,0 - 5,0	10.900.040.095	500
	11,0	4,5 - 6,5	10.900.040.110	500
	12,5	6,0 - 8,0	10.900.040.125	500
	14,5	7,5 - 10,0	10.900.040.145	500
dk 8,0 -0,4	dm 2,2	k 1,3 ±0,2	4,1 mm 1700 N 2700 N	

d	l ⁺¹	$\frac{d}{h}$	Nr.	
4,8	8,5	0,5 - 3,5	10.900.048.085	500
	9,5	3,0 - 5,0	10.900.048.095	500
	11,0	4,5 - 6,5	10.900.048.110	500
	13,0	6,0 - 8,0	10.900.048.130	500
	14,5	7,5 - 9,5	10.900.048.145	500
	16,0	9,0 - 11,0	10.900.048.160	500
	18,0	10,5 - 13,0	10.900.048.180	500
	21,0	12,5 - 16,0	10.900.048.210	500
	25,0	15,5 - 20,0	10.900.048.250	500
dk 9,5 -0,4	dm 2,7	k 1,5 ±0,2	4,9 mm 2480 N 3540 N	
6,4	12,5	1,5 - 6,5	10.900.064.125	500
	15,5	3,5 - 9,5	10.900.064.155	500
dk 13,0 -0,4	dm 3,7	k 2,0 ±0,3	6,5 mm 3760 N 5460 N	